

# The Axle Weighing Specialist



## Portable Static Scales



### Portable & Wireless Under-the-Wheel Weighing Solutions

**PT300™**  
Wheel Load Scales  
Pages 14-15



- ▶ Ultimate Versatility for Weighing on Virtually Any Surface
- ▶ Reduced Downtime with Industry-Leading Battery Life & Built-In Solar Charging
- ▶ Displays Single Scale Pad Values or Total Weight via RFX® Wireless Weighing

**PT300DW™**  
Wheel Load Scales  
Pages 16-17




- ▶ Ideal Weighing Solution for Any Vehicle with Dual or Large Flotation Tires
- ▶ Weigh Large Vehicles in Remote Locations for Maximum Efficiency
- ▶ Highly-Adaptable to Multiple Applications, from Agriculture to Transportation

**LP600™**  
Low-Profile Wheel Load Scales  
Pages 18-19



- ▶ Low-Profile for Easy Vehicle Approach and Positioning
- ▶ Scale Platform Accommodates Dual and Super-Single Tires
- ▶ Highly Portable for Weighing Axle Groups in Remote and Heavy-Haul Applications

**LP600-15T™**  
Portable Weighing Solution  
Pages 20-21



- ▶ Complete Static Axle Scale System with All Required Components
- ▶ Roll-Up Ramps Keep Axle Groups Level for Accurate Axle Weighing with Two Scale Pads
- ▶ Efficient Static Weighing for Higher Throughput Applications

**AX900™**  
Axle Load Scales  
Pages 22-23



- ▶ High-Volume Weighing for Indoor or Outdoor Applications with Multiple Indicator/Display Options
- ▶ Customizable for Above-Ground Portable or Flush-Mount, Pit-Style Applications
- ▶ Configurable Scales for Vehicles with Various Axle Spacings & Arrangements

IP RATING	IP67	IP67
NTEP CERTIFIED MODELS AVAILABLE	Class III	Class III
ACCURACY	± 1% of Reading	± 1% of Reading
CAPACITY	Pad Capacity up to 25,000 lb (11,300 kg)	Pad Capacity up to 40,000 lb (20,000 kg)
DISPLAY	5.5-Digit LCD with 1" (25 mm) Characters	5.5-Digit LCD with 1" (25 mm) Characters
BATTERY LIFE (CONTINUOUS USE)	Solar Power Provides up to One Year of Battery Life w/ Daytime, Outdoor Use	Solar Power Provides up to One Year of Battery Life w/ Daytime, Outdoor Use
BATTERY TYPE (PER SCALE PAD)	(4) AA NiMH	(4) AA NiMH
PAD DIMENSIONS (L x W x H)	12" x 12" x 3" (305 x 305 x 76 mm)	14" x 22" x 3" (356 x 559 x 76 mm)
SCALE WEIGHT	37 lb (17 kg)	49 lb (22 kg)

IP67	IP67	IP67
Class III	Class III	Class III
± 1% of Reading	± 1% of Reading	± 0.1% of Reading
Pad Capacity up to 30,000 lb (15,000 kg)	System Capacity up to 60,000 lb (30,000 kg)	System Capacity up to 180,000 lb (80,000 kg)
5.5-Digit LCD with 1" (25 mm) Characters	5.5-Digit LCD with 1" (25 mm) Characters	n/a
Solar Power Provides up to One Year of Battery Life w/ Daytime, Outdoor Use	Solar Power Provides up to One Year of Battery Life w/ Daytime, Outdoor Use	Up to 300 hours
(4) AA NiMH	(4) AA NiMH	(4) D Alkaline
LP600™: 22.5" x 15" x 1.5" (559 x 381 x 38 mm) LP630™: 30" x 15" x 1.7" (762 x 381 x 43 mm)	LP600-10T: 22" x 15" x 1.5" (559 x 381 x 38 mm) LP600-15T: 22" x 15" x 1.7" (559 x 381 x 43 mm) LP630-15T: 30" x 15" x 1.7" (762 x 381 x 43 mm)	Varies. See Page 23 for details
LP600™: 51 lb (23 kg) LP630™: 69 lb (31 kg)	LP600-10T: 47 lb (21 kg) LP600-15T: 47 lb (21 kg) LP630-15T: 69 lb (31 kg)	Starting at 700 lb (317 kg)

