

### NATIONAL TYPE EVALUATION PROGRAM

# Certificate of Conformance for Weighing and Measuring Devices

For:

**Indicating Element** 

Electronic, Non-Computing

Model: US-2011 and US-2011SS Series

n<sub>max</sub>: 6000

Accuracy Class: III

## **Submitted By:**

**USA** Measurements 4005 W. Reno Ave

Suite E

Las Vegas, NV 89118 Tel: 800-711-2237 Contact: Fred Herrmann

Email: sales@usameasurements.com Web site: www.usameasurements.com

# **Standard Features and Options**

- US-2011= Plastic Housing
- US-2011SS = Stainless Steel Housing
  - Automatic Zero Tracking (AZT)
  - Initial Zero Setting Mechanism (IZSM) 0
  - Automatic Zero Setting Mechanism (AZT) 0
  - Semi-Automatic Zero (Push Button) Zero 0
  - Semi-Automatic (Push Button) Tare 0
  - 0 AC Power
  - DC/Battery Power 0
  - Gross/Net Display 0
  - RS-232 0
  - Wireless Printer Feature 0
  - **Battery Saving Feature** 0
  - LCD Display 0
  - Motion Detection 0
  - Unit Key 0
  - lb/oz/kg/g units 0
  - Battery Operation with Low Battery Indication 0
  - Gross/Net Display 0
  - Gross/Net Weight Accumulation

Temperature Range: -10 °C to 40 °C (14 °F to 104 °F)


This device was evaluated under the National Type Evaluation Program and was found to comply with the applicable technical requirements of "NIST Handbook 44: Specifications, Tolerances and Other Technical Requirements for Weighing and Measuring Devices." Evaluation results and device characteristics necessary for inspection and use in commerce are on the following pages.

Chairman, NCWM, Inc.

kephen Benjamin Committee Chair, NTEP Committee

Issued: December 17, 2019

## 1135 M Street, Suite 110 / Lincoln, Nebraska 68508







### **USA Measurements**

Indicating Element / US-2011 & US-2011SS

<u>Application</u>: General purpose indicating element when connected to an NTEP certified and compatible weighing/load-receiving element.

<u>Identification</u>: The self-destructive identification badge may be found on the back of the indicating element.

Sealing: A lead wire security seal must be used by sealing two (2) predrilled sealing screws on the back of the indicator.

<u>Test Conditions:</u> This Certificate of Conformance supersedes Certificate of Conformance Number 19-132 and was issued to indicate a company phone number change. No additional testing was required. Previous test conditions are listed below for reference.

<u>Certificate of Conformance Number 19-132</u>: This certificate is issued based upon the following tests and upon information provided by the manufacturer. The Model(s) US-2011, US-2011SS, and digital weight indicators were submitted for this evaluation. The emphasis of the evaluation was on device design, operation, and compliance with influence factor requirements. The indicator was interfaced with a load cell simulator and then tested for accuracy over a temperature range of -10 °C to 40 °C (14 °F to 104 °F). The indicators were interfaced with a load receiving element, Tscale PB4252, and a printer. The device was tested for discrimination, power interruption, zero tests, and print format. Additionally, the device was tested with a supply voltage of 100VAC to 130VAC and 5.8VDC to 7.2VDC.

Evaluated By: E. A. Payne, Jr (MD) 19-132; M. Manheim (NCWM) 19-132A1

<u>Type Evaluation Criteria Used</u>: *NIST Handbook 44 Specifications, Tolerances, and Other Technical Requirements for Weighing and Measuring Devices*, 2012 Edition. *NCWM Publication 14 Measuring Devices*, 2012 Edition.

<u>Conclusion</u>: The results of the evaluation and information provided by the manufacturer indicate the device complies with applicable requirements.

Information Reviewed By: D. Flocken (NCWM) 19-132, 19-132A1


### Example(s) of Device:





Model US-2011SS

Model US-2011







# **USA Measurements**

Indicating Element / US-2011 & US-2011SS





Model US-2011SS

Model US-2011

