

## US-PTP-II Thermal Printer



### **Feature:**

- Portable device suited for outdoor usage
- Black mark paper location sensor
- Low battery indicator (7.4V,1500mAh)
- Equipped with lithium battery for 8 hours continuous work
- Vairous interface communication and interface capabilities
- Easy paper loading
- High printing speed, up to 90mm/s

### **Application:**

- Mobile POS/Retail
- Hospitality
- Packing citation
- Deliveries
- Onboard Transportation
- Field reparts/Installation
- Warehouse/ logistics
- Utility billing/meter reading

**Specification:**

Model	PTP-II
Dimension	79*110*45mm
Print method	Line thermal printer
Paper width	57mm
print width	48mm
Weight ( g)	235 (not including the paper roll)
Max diameter of paper roll	40mm
Dot per line	384 dots/line
internal characters	ASCII CH(8x16,9x17,9x24,12x24); GBK(16x16,24x24)
Print speed	50~80mm/s
Life cycle time	50km(printing density under 12.5%)/100 million pulses
text and graphic Support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode (CODE39EAN13EAN8 CODABARCODE128CODE93ITF) QR code ,PDF417
Dot pitch (resolution)	203DPI/8 dots/mm
interface	WIFI+Mini USB
Power	1500mAh 7.4V rechargeable Lithium battery
Recharge adapter	Stand by recharging / AC adapter
Self-check	Without paper / cover open
Black mark test	Supported
Paper feeding	Easy paper loading
commands	ESC/POS compatible with order sets
Paper cut	By hands
operate setting	Temperature -10°C~50°C ; Humidity 20%~85%
Recharge Setting	Temperature 5°C~40°C; Humidity 20%~85%
Storage Setting	Temperature -20°C~70°C ; Humidity 5%~95%
Standard accessories	Long-term preservable paper, AC adapter, li-ion battery. USB cable
Optional accessories	CD,leather case