

DESKTOP LABEL PRINTER OS-2130D



USA Measurements
"We Outmeasure the Competition"



FRED'S PERSONAL GUARANTEE

- Easy to setup
- Easy to use
- Easy replacement parts
- Easy calibration/phone support
- Long warranty support
- 30 day money back guarantee
- Lowest price guarantee

CALL NOW: 858-484-8000



Flank Steak	
PACKED ON SELL BY WT/LBS. 04.18.11 04.19.11 0.55	
2.99	1.64
PRICE PER LB.	TOTAL PRICE
USA Measurements 4005 W Reno Ave Ste E Las Vegas, NV 89118	
SAFE HANDLING INSTRUCTIONS THIS PRODUCT IS NOT TO BE CONSUMED. IT IS A MEAT PRODUCT. IT MUST BE KEPT FROZEN AT ALL TIMES. IT MUST BE KEPT FROZEN UNTIL READY TO BE THAWED. IT MUST BE THAWED IN THE ORIGINAL PACKAGING. IT MUST BE COOKED TO AN INTERNAL TEMPERATURE OF 160°F. IT MUST BE REHEATED TO AN INTERNAL TEMPERATURE OF 165°F. IT MUST BE CONSUMED IMMEDIATELY AFTER REHEATING.	

Chicken Thighs	
0.86	0
04.18.11 04.19.11 4.92	2.99 14.71
PACKED ON SELL BY INET/LBS PRICE PER LB.	TOTAL PRICE
USA Measurements 4005 W Reno Ave Ste E Las Vegas, NV 89118	
SAFE HANDLING INSTRUCTIONS THIS PRODUCT IS NOT TO BE CONSUMED. IT IS A MEAT PRODUCT. IT MUST BE KEPT FROZEN AT ALL TIMES. IT MUST BE KEPT FROZEN UNTIL READY TO BE THAWED. IT MUST BE THAWED IN THE ORIGINAL PACKAGING. IT MUST BE COOKED TO AN INTERNAL TEMPERATURE OF 165°F. IT MUST BE REHEATED TO AN INTERNAL TEMPERATURE OF 165°F. IT MUST BE CONSUMED IMMEDIATELY AFTER REHEATING.	

Ribeye Steak	
0.93	0
04.18.11 04.19.11 4.93	
2.99	14.74
PRICE PER LB.	TOTAL PRICE
USA Measurements 4005 W Reno Ave Ste E Las Vegas, NV 89118	

Salmon Fillet	
0.23	0
04.18.11 04.19.11 10.95	
2.99	32.74
PRICE PER LB.	TOTAL PRICE
USA Measurements 4005 W Reno Ave Ste E Las Vegas, NV 89118	

Ground Beef	
0.23	0
04.18.11 04.19.11 0.41	2.99 1.23
PACKED ON SELL BY WT/LBS PRICE PER LB.	TOTAL PRICE
USA Measurements 4005 W Reno Ave Ste E Las Vegas, NV 89118	

OS-2130D

The OS-2130D is a compact direct thermal desktop barcode printer that offers outstanding features and exceptional value. This easy-to-operate printer is ideal for low-to medium-volume printing needs. The OS-2130D is ideal for applications such as point-of-sale, weight scales, mailing, banking, ticketing, patient tracking kiosks, and document labeling.

Key features of the OS-2130D include a USB port, an internal real time clock (RTC) and a buzzer. The USB allows easy connectivity with computers and other devices. The internal RTC facilitates time and date marking for standalone operation. The buzzer provides built-in error warning by beeping when media runs out or paper jams occur. With its easy operation, reliability, and space-saving size, the OS-2130D offers a high performance, cost-effective solution for your barcode and labeling requirements.

Specifications	OS-2130D
Printing Methods	Direct thermal
Printing Resolution	203 DPI (8 dots/mm)
Printing Speed	2ips ~ up to 4ips (51~ 102mm/s)
Printing Length	Max 100" (2540mm)
Printing Width	Max 2.83" (72mm), Min 1" (25.4mm)
Memory	8MB SDRAM (6MB user available), 4mb Flash ROM(2MB user available)
CPU Type	32 bit RISC microprocessor 100MHz
Sensors	Reflective (Left side)
Operation Interface	Button (Feed) x 1
Communication Interface	RS-232, USB, Cash drawer
Fonts	Internal character sets standard 5 alpha-numeric fonts from 0.049"H ~ 0.23" (1.25mm ~ 6.0mm) Internal fonts are expandable to 24x24 4 direction 0 ~ 270 rotation Soft fonts and 2-byte Asian fonts are downloadable Ability to print any windows True Type Font easily
1D Barcodes	<u>PPLA</u> : Code 39 (Standard/with checksum digit), Code 93 Interleaves 2 of 5 (standard/with checksum digit/with human readable check digit), EAN-8, EAN-13, UPC-A, UPC-E, UCC/EAN-128, Random Weight, Plessey, HBIC, Telepen, FIM, UPC2, UPC5, GS1 DataBar <u>PPLB</u> : Code 39 (Standard/with checksum digit), Code 93 Interleaves 2 of 5 (standard/with checksum digit/with human readable check digit), EAN-8 (Standard/2 digit add-on/5 digit add-on) , EAN-13 (Standard/2 digit add-on/5 digit add-on), UPC-A (Standard/2 digit add-on/5 digit add-on), UPC-E (Standard/2 digit add-on/5 digit add-on), Postnet, Codebar, Code 128 subset A/B/C, Code 128 UCC (Shipping Container Code) 128 Auto, German, Postcode, Matrix 2 of 5, UCC/EAN 128, UPC Interleaved 2 of 5, GS1 Data Bar
2D Barcodes	PPLA/PPLB: MaxiCode, PDF417, Data Matrix (ECC 200 only), QR code, Composite codes
Graphics	PPLA/PPLB: PCX, BMP, IMG, HEX, GDI, Binary raster (PPLB Only)
Emulation	PPLA/PPLB
Software - Label editing	Windows Driver (XP/ Vista/ Win 7) Bar Tender from Seagull Scientific
Software - Utility	Printer Utility - Font Utility
Media Type	Roll-feed, die-cut. continuous, fan-fold, tags, ticket in thermal paper
Media	Max width 3.14" (79.8mm) Min width 1" (25.4mm) Max Length 100" (2540mm) Min Length: 0.196" (5mm) Thickness 0.0025"~0.01" (0.06535mm~0.254mm) Max roll capacity core 0.5" / OD 4.3" (109mm), or core 1" / OD 4 (102mm) Core size 0.5"(12,7mm) and 1"(25.4mm) ID
Dimensions	W 134 x H 163 x L 228 mm
Dimensions	1.2kgs
Power Source	100V~240V, 1.8A, 50~60Hz Input 24V, 2.5A Typical, Output
Operation Environment	Operation Temperature: 40° F~100°F (4°C~38°C), 10% ~ 90% non-condensing, Storage Temperature: -4° F~122°F (-20°C~50°C)
Other	Buzzer build-in & internal real time clock
Optional Items	Guillotine Cutter, Peeler, External 8" OD media stacker
Agency Listing	

FEATURES

- For low and medium volume printing demand
- 2.83-inch (72mm) printing width, direct thermal barcode printer
- 203 dpi print resolution and up to 4ips (102mm/s) printing speed
- 32-bit CPU and 4MB Flash: 8MB SDRAM memory standard
- Communication interfaces- Serial RS-232 (9 pin), USB, Cash Drawer, to fit in various systems



- Buzzer for error warning function
- internal Real Time Clock
- Support Windows 7
- Tear off bar Built-in



- Media Guide Design for paper stabilized





www.usameasurements.com

USA Measurements Information

sales@usameasurements.com
4005 W Reno Ave STE E Las Vegas,
NV 89118, Tel: (800) 711-2237

* This data sheet is for informational purposes only. Usa Measurements makes no warranties, expressed or implied in this summary. Specifications are subject to change without notice. All trademarks are the property of their respective owners. More specific information, please refer to the user's manual.