

VGW Series

6,000 g x 0.1 g 10,000 g x 0.1 g 15,000 g x 0.1 g 20,000 g x 0.1 g

Hi-Lo-Go Check Weighing w/ Audible Warning

IGW

- Rechargeable Battery: up to 200 hrs.
- Bi-Directional RS232 Interface
- 3 Color LCD Display
- Units: kg, g, lb
- Accumulation & Counting
- Dual Display Optional



Made in Democratic Taiwan

## VGW Series



## A Higher Level of Precision....A Higher Level of Performance

Model	VGW-6001	VGW-10001	VGW-15001	VGW-20001	
Capacity	6,000 g 13.2 lb	10,000 g 22 lb	15,000 g 33 lb	20,000 g 44 lb	
Readability	0.1 g / 0.002 lb				
Repeatability (Std. Dev.)	± 0.2 g				
Linearity	±.0.3 g				
Weighing Units	kg, g, lb	kg, g, lb			
Functions	Counting, Checkw	Counting, Checkweighing, Piece Counting			
Tare Range	To Capacity by Su	To Capacity by Subtraction			
Power Source	Internal Rechargeable Battery, AC/DC Adaptor				
Construction	Static Resistant ABS, Stainless Steel Pan				
Display	3 Color LCD Display				
Pan Size	9.24 x 9.86 / 230 x	9.24 x 9.86 / 230 x 250 mm with Stainless Steel Insert			
Dimensions (W x D x H)	9.4 x 11.2 x 4.1 in /	9.4 x 11.2 x 4.1 in / 240 x 285 x 105 mm			
Operating Environment	41 °F to 95 °F / 5 °	41 °F to 95 °F / 5 °C to 35 °C, Temperature Fluctuation $\leq$ 5 °C / hour, Humidity 50% to 85% RH			
Connectivity	RS 232 Interface,	RS 232 Interface, Selectable Transmission Modes			
Net Weight	5.0 lb / 2.2 kg				
Shipping Weight	7.5 lb / 3.4 kg	7.5 lb / 3.4 kg			
Options	RS-232 Cable Connection, Printer, Carrying Case				

Features	Benefits	
3 Color LCD	For Check Weighing (Red, Green, Yellow)	
Rechargeable Battery Operation	Up to 200 hrs. of Operation	
Large Stainless Steel Pan	Allows for Easy Weighing of Large Objects	
Simple Piece Counting	Counting of Small Parts for Inventory Use	
Bright, 3 Color Backlit LCD Display	Easy to Read in all Lighting Conditions Including Bright Sunlight	
Multiple Weighing Units	Allows Flexibility of Weighing	
Leveling Feet	The Balance Remains Level for Accurate Results Even on Uneven Working Surfaces	
Battery Operation	Portability - can be used in Various Locations without Access to a Wall Outlet	
Configurable RS 232 Interface	Allows Communication with Peripheral Data Collection and Printing Instruments	
Hi-Lo-Go Checkweighing	Checkweighing with Color Changing LCD and Audible Alarm	
Compact Design	Perfect for Space Efficiency and Mobility	
Optional Dual Display	Ability to add a Dual Display for Deli Style Applications	