



Road
Manager

Road Vocation, Agile Interface and Graphic Display 7"

Special features

- LCD graphic display 6.1 x 3.15" (154.1 x 80mm);
- Truck in/out, 1000 ID memory;
- Time and date;
- Current loop for remote display;
- Two RS232 serial ports;
- Mini QWERTY keyboard included for fast typing;
- Power up to 16, 350 ohms load cells;
- Saves up to 2,000 weighings;
- Works with digital or analog load cells;
- Stainless Steel NEMA 4X;
- Prints ticket with TM-298 or LX-350;
- Two-year limited warranty.

SPECIFICATION

Hardware	Voltage range: 85~245 Vcc		
	Consumption: 10W		
	Operating Temperature: -10°C ~ 40°C		
	Protection Degree: IP-65		
	Material: Stainless steel		
Interface	Graphic Display TFT 7" RGB 800x480 pixels		
	Frontal painel with 25 keys, including quick navigation		
	Keyboard QWERTY (standard mini DIN PS/2 USB conector) + quick navigation keys (F1 to F12)		
	Serial output to printers Epson LX300 or Bematech MP-20		
	Loop current output for remote displays DR-WT75, DR-WT125 or DR-WT200		
	Serial output RS232 or RS485 (two wires) to comunication with PC and other devices		
	Ethernet Comunication (optional)		
Road operations	Allows single weighing		
	Stores up to 32768 weighing records		
	Base with up to 1600 clients and 1600 products pre-registered		
	Base with up to 40 pre-registered tares, allowing manual tare		
	Up to 14 tips of discounts		
	Prints weighing tickets		
	Various options for reports		
	Up to 16 digital or analog load cells		
Details of Road System	Storage of weighing datas	ID (auto increment)	
		Time and Date	
		Vehicle Plate	
		Customer ID	
		Product ID	
		Invoice	
		Silo	
		Driver	
		Identification document	
		Type of freight	
		Lot number	
	Applicable discounts	PH	Moisture break
		PHM	Tax
		Faulty	Technical break
		Defective	Cleaning/Drying
		Defective break	Brokes
		Impurities	Humidity
		Impurities break	Others

COMPONENTS LIST



Sealing screw



Cable gland in stainless steel



Lock-nut in stainless steel




Power cable



Bracket fixing knob



Battery lithium 3V 20mm



Power supply PWR08A



Washer




Nylon spacer



Screw M3 x 0,5



USB QWERTY Keyboard



TFT Display 7"



Housing in stainless steel



Main board



Panel with keyboard



Flat cable



LX300 printer cable



Serial RS232 cable



QWERTY Keyboard cable

DIMENSIONS (mm - inches)

