

C A M B R I D G E

DIGITAL WEIGHT INDICATOR MODEL SSCSW-10AT & SSCSW-10AT-B



Applications:

- Floor Scales
- Bench Scales
- Hopper Scales
- Tank Scales
- Fork Lift Scales
- General Purpose Weighing
- Remote Display Configuration

Standard Features Include:

- Stainless Steel NEMA 4X Enclosure with Stainless Steel Swivel Stand
- Selectable: NTEP 5,000 Divisions
Non-NTEP 20,000 Divisions
- Net/Gross Display Modes
- Full Range Auto Tare
- Adjustable Digital Filtering
- All Pushbutton Controls
- LED Display (Bright)
- Printer Data Output on Demand
- Clearly, Visible Center of Zero Indication on Display
- Keypad Calibration with Audit Trail
- Weight Totalization
- Lb/Kg Conversion
- 1 to 5 Points of Digital Calibration
- Span Adjustment at Increasing or Decreasing Weights
- Full Range Push Button Zero
- (1) RS-232 Port for Interface with:
 - Printer Output of Gross/Tare/Net
 - Computer Data Output
 - Scoreboard Continuous Output Alphanumeric or Numeric
- 100-240 VAC, 50/60 Hz Power Cord
- Auto Zero Tracking
- Adjustable Motion Detection
- (6) Pin Water-Tight Signal Connection

Approvals:



COC # 06-070A1



MEASUREMENT CANADA
AM-5778C



Made in USA

Members:

- THE NATIONAL CONFERENCE ON WEIGHTS AND MEASURES
- THE INTERNATIONAL SOCIETY OF WEIGHING AND MEASUREMENT

CAMBRIDGE

DIGITAL WEIGHT INDICATOR MODEL SSCSW-10AT & SSCSW-10AT-B

Model SSCSW-10AT-B

For portable applications where battery operation is required. Includes all standard SSCSW-10AT features plus:

- Battery/AC Operation
- Internal Battery Charger
- Internal Lithium-Ion Battery
- Sleep Mode

Optional Features:

Models SSCSW-10AT & SSCSW-10AT-B

- 110 VAC Dry Contact Set Point
- Peak Weight Hold
- Digital Scroll Tare
- Ethernet Connection
- Wi-Fi Link to Customers Wireless Hub 802.11 B/G

Contact Cambridge for Additional Options



Cambridge Model SSCSW-10AT-B

Specifications

Description

Power - Model SSCSW-10AT	100-240 VAC, 50/60 Hz AC Power Cord
Power - Model SSCSW-10AT-B	7.4 VDC 3000 mA [*] Battery, 100-240 VAC, 50/60 Hz
Humidity	0-90% Non-condensing
Enclosure	304 Stainless Steel NEMA 4X
Dimensions	7.5" x 4.5" x 3" without Stand, +1 inch with Stand
Resolution	NTEP: 5,000 Division, NON-NTEP: 20,000 Division
Display	High Efficient, Bright (adjustable) LED—6 Digits—.56" High
Input	0-15mv
Temperature	-10° to +40° Celsius
Linearity	0.001% of Full Scale
Accuracy	0.001% of Full Scale
Load Cell Supply	5VDC at 150ma (8 each 350 ohm load cells)

* (1) 350 OHM Cell - 22hrs / (4) 350 OHM Cell - 20hrs / (8) 350 OHM Cell - 14hrs

Print Format Samples

Sample Ticket:

Gross(lb): 1200
Tare(lb): 200
Net(lb): 1000

Sample Ticket with Totalization:

Wt# 1 550
Wt# 2 450
Total Wt. 1000 lb

Distributed By: