

# LCTx Series

Specifications						
Model Suffix	3	7	16	33	66	110
Casing	Plastic					
Capacity	3.3lb	7lb	16lb	33lb	66lb	110lb
2nd Capacity	No					
Resolution	0.00005lb	0.0001lb	0.0002lb	0.0005lb	0.001lb	0.002lb
Display Divisions	66,000	70,000	80,000	66,000	66,000	55,000
Internal Resolutions	20 Million					
Accuracy	+/-2d					
Platter Size(inch)	9 x 13.25					
Draft Shield	No					
Dimensions(inch)	11.5 x 10 x 5					
LCD Size(inch)	3 x 2.5 (3 rows)					
Beeper	Yes,Selectable					
Auto Backlight	Yes,Selectable					
Auto Shut Off	Yes,Selectable					
Auto Hold	No					
Unit Switching	kg,lb.					
AD Processor	32 bit A/D					
AD Update Speed	12.5Hz					
Settling Time	<2s					
Calibration Software	AnyCAL					
No. of Keys	30					
Memory	9					
Counting Function	Yes					
RS232C	No					
USB	No					
Battery	7.4V 2200mAh Li Rechargeable					
AC Adapter	Yes, 12VDC					
Operating Environment	0°C-40°C / 32°F-104°F					
Standard Accessories	Manual, AC Adapter, Rechargeable battery					
Additional Accessories	None					
<b>2 - Year Manufacturer Warranty</b>						

