

LVS-S Series

Specifications

Model Suffix	700	
Casing	Stainless Steel	
Capacity	700lb	
2nd Capacity	No	
Resolution (lb)	0.2lb	
Resolution (kg)	0.1kg	
Display Divisions	3,500	
Internal Resolutions	2 Million	
Accuracy	+/-3d	
Platter Size(inch)	37.5 x 19.75	44 x 22
Dimensions(inch)	37.5 x 19.75 x 3	44 x 22 x 3
LCD Size(inch)	1.25 x 3.625	
Cable Length	12 inches	
Beeper	Yes, Selectable	
Auto Backlight	Yes, Selectable	
Auto Shut Off	Yes, Selectable	
Auto Hold	No	
Unit Switching	kg, lb	
AD Processor	21 bit A/D	
AD Update Speed	10Hz	
Settling Time	<2s	
Calibration Software	AnyCAL	
No. of Keys	5	
Memory	Zero	
Counting Function	No	
RS232C	Yes	
USB	No	
Battery	Yes, 6 x AA Battery	
AC Adapter	Yes, 9VDC	
Operating Environment	0°C-40°C / 32°F-104°F	
Standard Accessories	Manual, AC Adapter, Rubber mat	
Additional Accessories	None	

2 - Year Manufacturer Warranty

