

# LVS + Dual Series

## Specifications

<b>Model Suffix</b>	700 XL
<b>Casing</b>	Stainless Steel
<b>Capacity</b>	700lb
<b>2nd Capacity</b>	No
<b>Resolution (lb)</b>	0.2lb
<b>Resolution (kg)</b>	0.1kg
<b>Display Divisions</b>	3,500
<b>Internal Resolutions</b>	2 Million
<b>Accuracy</b>	+/-3d
<b>Platter Size(inch)</b>	42 x 22
<b>Dimensions(inch)</b>	42 x 22 x 3
<b>LCD Size(inch)</b>	1.25 x 3.625
<b>Cable Length</b>	99 inches
<b>Beeper</b>	Yes, Selectable
<b>Auto Backlight</b>	Yes, Selectable
<b>Auto Shut Off</b>	Yes, Selectable
<b>Auto Hold</b>	No
<b>Unit Switching</b>	kg, lb
<b>AD Processor</b>	21 bit A/D
<b>AD Update Speed</b>	10Hz
<b>Settling Time</b>	<2s
<b>Calibration Software</b>	AnyCAL
<b>No. of Keys</b>	5
<b>Memory</b>	Zero
<b>Counting Function</b>	No
<b>RS232C</b>	Yes
<b>USB</b>	No
<b>Battery</b>	7.4V 2200mAh Li Rechargeable
<b>AC Adapter</b>	Yes, 12VDC
<b>Operating Environment</b>	0°C-40°C / 32°F-104°F
<b>Standard Accessories</b>	Manual, AC Adapter, Rubber mat, Com Cable
<b>Additional Accessories</b>	None

**2 - Year Manufacturer Warranty**

