

SCT Series

Specifications

Model Suffix	600	1200	7	16	33
Casing	Plastic				
Capacity	600g	1200g	7lb	16lb	33lb
2nd Capacity	No				
Resolution	0.01g	0.02g	0.0001lb	0.0002lb	0.0005lb
Display Divisions	60,000		70,000	80,000	66,000
Internal Resolutions	16 Million				
Accuracy	+/-2d				
Platter Size(inch)	7.5 x 10				
Draft Shield	No				
Dimensions(inch)	12.5 x 8.5 x 3		8.5 x 13 x 4		
LCD Size(inch)	3 x 2.5 (3 rows)				
Beeper	Yes,Selectable				
Auto Backlight	Yes,Selectable				
Auto Shut Off	Yes,Selectable				
Auto Hold	No				
Unit Switching	g,lb				
AD Processor	24 bit A/D				
AD Update Speed	7.5Hz				
Settling Time	<2s				
Calibration Software	AnyCAL				
No. of Keys	20				
Memory	1				
Counting Function	Yes				
RS232C	No				
USB	No				
Battery	Yes, Rechargeable				
AC Adapter	Yes, 12VDC				
Operating Environment	0°C-40°C / 32°F-104°F				
Standard Accessories	Manual, AC Adapter, Rechargeable battery				
Additional Accessories	None				

2 - Year Manufacturer Warranty

