

PORTABLE WEIGHING INDICATOR · WIRED

US-M5A Weighing Indicator

Wired portable indicator for aircraft, crane outrigger, and heavy equipment weighing up to 500 ton



WHY OPERATORS CHOOSE THE US-M5A

- ✓ **500 Ton** maximum weighing capacity
- ✓ **Class III** static weighing accuracy
- ✓ **Wired Connection** for signal stability
- ✓ **Built-in Thermal Printer** for on-the-spot tickets
- ✓ **Rechargeable Battery**, backlit LCD display
- ✓ **IP-rated Hard Case** for field transport

PACKAGE INCLUDES

The US-M5A ships as a complete portable weighing indicator, ready to pair with compatible weighing pads and platforms:

- ✓ US-M5A weighing indicator
- ✓ IP-rated hard transport case
- ✓ Built-in thermal printer
- ✓ Rechargeable battery pack
- ✓ Power adapter
- ✓ RS-232 and USB output ports
- ✓ Operator documentation

The US-M5A is a wired portable weighing indicator built for aircraft weighing, crane outrigger weighing, and heavy off-road equipment. Class III static accuracy, up to 500 ton maximum capacity, and a built-in thermal printer let operators capture weight readings and print tickets on the spot. The rechargeable battery, backlit LCD, and IP-rated hard case make the US-M5A a field-ready indicator for hangar, jobsite, and outdoor deployment.

Contact us for a configured quote 800-917-7205 · sales@primeusascals.com

Prime USA Scales

3915 W Hacienda Ave, Suite A-117, Las Vegas, NV 89118 | **800-917-7205** | sales@primeusascals.com | primeusascals.com

US-M5A · FEATURES, SPECIFICATIONS, AND APPLICATIONS

PAGE 2 OF 2



RS-232 and USB ports for data output and printing



Built-in thermal printer for on-the-spot weight tickets

STANDARD FEATURES

- ✓ Wired portable weighing indicator
- ✓ Class III static weighing accuracy
- ✓ Up to 500 ton maximum capacity
- ✓ Backlit LCD with large digit display
- ✓ Pound display
- ✓ Hold, Tare, Zero, Gross, Net functions
- ✓ Built-in thermal printer
- ✓ Rechargeable battery pack
- ✓ RS-232 output port
- ✓ USB output port
- ✓ IP-rated hard transport case
- ✓ English language default interface

SPECIFICATIONS

Model	US-M5A
Type	Wired portable indicator
Accuracy	Class III static
Max Capacity	500 ton
Resolution	100,000
Sampling Rate	200 times per second
Display Rate	12.5 times per second
Display Unit	Pound
Channel Inputs	1 to 4 channels
Communication	RS-232, USB
Printer	Built-in thermal
Power	Rechargeable battery
Enclosure	IP-rated hard case

TYPICAL APPLICATIONS

- ✓ Aircraft weighing (static)
- ✓ Crane outrigger weighing
- ✓ Haul truck axle weighing
- ✓ Heavy off-road equipment
- ✓ Portable field weighing
- ✓ Compatible load-pad systems

500 TON
MAX CAPACITY

CLASS III
STATIC ACCURACY

RS-232 + USB
OUTPUT PORTS

THERMAL
BUILT-IN PRINTER

Prime USA Scales

3915 W Hacienda Ave, Suite A-117, Las Vegas, NV 89118 | **800-917-7205** | sales@primeusascals.com | primeusascals.com