NTEP APPROVED

PRIME USA SCALES — DIGITAL WEIGHING INDICATOR

US-6011 Digital Indicator

LCD & LED Models · Stainless Steel or Mild Steel Enclosure

primeusascales.com
(800) 917-7205
sales@primeusascales.com

USA Measurements
"We Outmeasure the Competition"

US-6011MS-LCD



US-6011MS-LED



NTEP APPROVED | 5,000 DIVISIONS | RS-232 PORT | BATTERY BACKUP

MODELS AVAILABLE

US-6011MS-LED	Mild Steel enclosure · Red LED digits · Units: lb, kg
US-6011SS-LED	Stainless Steel enclosure · Red LED digits · Units: lb, kg
US-6011MS-LCD	Mild Steel enclosure · Black LCD digits · Units: lb, kg, oz, lb:oz, g
US-6011SS-LCD	Stainless Steel enclosure · Black LCD digits · Units: lb, kg, oz, lb:oz, g

WHAT'S INCLUDED

- ✓ US-6011 Digital Indicator
- ✓ SS Mounting Bracket
- ✓ Spare Connectors
- ✓ 15′ SS Braided Cable
- ✓ User Manual
- ✓ Rechargeable Battery
- ✓ (2) Adjustable Knobs
- ✓ Plastic Splash Guard
- ✓ 110V Power Adapter

OPTIONAL ACCESSORIES

- + Thermal Printer
- + Remote Display 3″
- + Outdoor Display 6″
- + Heavy Duty Stand
- + Label Printer
- + Remote Display 5″
- + Indicator Stand (SS)
- + Cal. Certificate

INDICATOR FEATURES

- 1″ digit display — LED (red) or LCD (black) models
- Gross weighing with multiple tare functions
- Pre-set tare and zero button
- Multiple hold functions
- Counting pieces function
- Accumulation / batch weighing
- Over/Under checking with alarm
- Power saving mode
- Automatic date and time update
- Modify gravity based on location
- 100% manual zero range setting
- Automatic error warning alarm
- Splash-proof keyboard and display
- RS-232 port for scoreboard display
- RS-232 port for connecting to printer
- Displays up to 50,000 graduations
- Full duplex RS-232 serial port
- Powers up to six 350Ω load cells
- Easy 5-step calibration
- NTEP approved — 5,000 divisions

TECHNICAL SPECIFICATIONS

Display	1″ LED (red) or LCD (black) digits
Weighing Units (LCD)	lb, kg, oz, lb:oz, g
Weighing Units (LED)	lb, kg
Max Graduations	50,000 (NTEP: 5,000 divisions)
Load Cell Drive	Powers up to six 350Ω load cells
Communication	Full duplex RS-232 serial port
Power	110V adapter + rechargeable battery backup
Enclosure (MS)	Mild steel — standard environments
Enclosure (SS)	Stainless steel — wash-down environments
Warranty	2-year manufacturer warranty
NTEP	Legal for trade · 5,000 divisions

COMPATIBLE / REPLACES

MS-7510 | OP-900 | SL-7510 | SL-900 | LP-7510 | OP-902

COMMON APPLICATIONS

Prime USA Scales
4445 Harmon Cove Ct, Suite 7 · Las Vegas, NV 89103
(800) 917-7205 · sales@primeusascales.com · primeusascales.com

NTEP Approved

Livestock Scales	Cattle, hogs, sheep
Crane Scales	Overhead hoisting, scrap metal
Tank / Hopper	Batch processing, fill-by-weight
Truck Scales	Axle and platform weighing