

US-6011 Digital Indicator

LCD & LED Models · Stainless Steel or Mild Steel Enclosure



USA Measurements
"We Outmeasure the Competition"



US-6011MS-LCD



US-6011MS-LED



NTEP APPROVED

5,000 DIVISIONS

RS-232 PORT

BATTERY BACKUP

MODELS AVAILABLE

US-6011MS-LED	Mild Steel enclosure · Red LED digits · Units: lb, kg
US-6011SS-LED	Stainless Steel enclosure · Red LED digits · Units: lb, kg
US-6011MS-LCD	Mild Steel enclosure · Black LCD digits · Units: lb, kg, oz, lb:oz, g
US-6011SS-LCD	Stainless Steel enclosure · Black LCD digits · Units: lb, kg, oz, lb:oz, g

WHAT'S INCLUDED

✓ US-6011 Digital Indicator	✓ Rechargeable Battery
✓ SS Mounting Bracket	✓ (2) Adjustable Knobs
✓ Spare Connectors	✓ Plastic Splash Guard
✓ 15' SS Braided Cable	✓ 110V Power Adapter
✓ User Manual	

OPTIONAL ACCESSORIES

+ Thermal Printer	+ Label Printer
+ Remote Display 3"	+ Remote Display 5"
+ Outdoor Display 6"	+ Indicator Stand (SS)
+ Heavy Duty Stand	+ Cal. Certificate

INDICATOR FEATURES

- ▶ 1" digit display — LED (red) or LCD (black) models
- ▶ Gross weighing with multiple tare functions
- ▶ Pre-set tare and zero button
- ▶ Multiple hold functions
- ▶ Counting pieces function
- ▶ Accumulation / batch weighing
- ▶ Over/Under checking with alarm
- ▶ Power saving mode
- ▶ Automatic date and time update
- ▶ Modify gravity based on location
- ▶ 100% manual zero range setting
- ▶ Automatic error warning alarm
- ▶ Splash-proof keyboard and display
- ▶ RS-232 port for scoreboard display
- ▶ RS-232 port for connecting to printer
- ▶ Displays up to 50,000 graduations
- ▶ Full duplex RS-232 serial port
- ▶ Powers up to six 350Ω load cells
- ▶ Easy 5-step calibration
- ▶ NTEP approved — 5,000 divisions

TECHNICAL SPECIFICATIONS

Display	1" LED (red) or LCD (black) digits
Weighing Units (LCD)	lb, kg, oz, lb:oz, g
Weighing Units (LED)	lb, kg
Max Graduations	50,000 (NTEP: 5,000 divisions)
Load Cell Drive	Powers up to six 350Ω load cells
Communication	Full duplex RS-232 serial port
Power	110V adapter + rechargeable battery backup
Enclosure (MS)	Mild steel — standard environments
Enclosure (SS)	Stainless steel — wash-down environments
Warranty	2-year manufacturer warranty
NTEP	Legal for trade · 5,000 divisions

COMPATIBLE / REPLACES

MS-7510 OP-900 SL-7510 SL-900 LP-7510 OP-902

COMMON APPLICATIONS

Prime USA Scales

3915 W Hacienda Ave, Suite A103 · Las Vegas, NV 89118

(800) 917-7205 · sales@primeusascalas.com · primeusascalas.com

NTEP
Approved

Livestock Scales	Cattle, hogs, sheep
Crane Scales	Overhead hoisting, scrap metal
Tank / Hopper	Batch processing, fill-by-weight
Truck Scales	Axle and platform weighing