PrimeUSAScales
"Best Scale at the Best Price"

800-917-7205
sales@primeusascales.com
primeusascales.com

PORTABLE WEIGHING INDICATOR · WIRED

US-M5A Weighing Indicator

Wired portable indicator for aircraft, crane outrigger, and heavy equipment weighing up to 500 ton



WHY OPERATORS CHOOSE THE US-M5A

- ✓ **500 Ton** maximum weighing capacity
- ✓ **Class III** static weighing accuracy
- ✓ **Wired Connection** for signal stability
- ✓ **Built-in Thermal Printer** for on-the-spot tickets
- ✓ **Rechargeable Battery**, backlit LCD display
- ✓ **IP-rated Hard Case** for field transport

PACKAGE INCLUDES

The US-M5A ships as a complete portable weighing indicator, ready to pair with compatible weighing pads and platforms:

- ✓ US-M5A weighing indicator
- ✓ IP-rated hard transport case
- ✓ Built-in thermal printer
- ✓ Rechargeable battery pack
- ✓ Power adapter
- ✓ RS-232 and USB output ports
- ✓ Operator documentation

The US-M5A is a wired portable weighing indicator built for aircraft weighing, crane outrigger weighing, and heavy off-road equipment. Class III static accuracy, up to 500 ton maximum capacity, and a built-in thermal printer let operators capture weight readings and print tickets on the spot. The rechargeable battery, backlit LCD, and IP-rated hard case make the US-M5A a field-ready indicator for hangar, jobsite, and outdoor deployment.

Contact us for a configured quote 800-917-7205 · sales@primeusascales.com

Prime USA Scales
"Best Scale at the Best Price"

800-917-7205
sales@primeusascales.com
primeusascales.com



RS-232 and USB ports for data output and printing



Built-in thermal printer for on-the-spot weight tickets

STANDARD FEATURES

- ✓ Wired portable weighing indicator
- ✓ Class III static weighing accuracy
- ✓ Up to 500 ton maximum capacity
- ✓ Backlit LCD with large digit display
- ✓ Pound display
- ✓ Hold, Tare, Zero, Gross, Net functions
- ✓ Built-in thermal printer
- ✓ Rechargeable battery pack
- ✓ RS-232 output port
- ✓ USB output port
- ✓ IP-rated hard transport case
- ✓ English language default interface

SPECIFICATIONS

Model	**US-M5A**
Type	**Wired portable indicator**
Accuracy	**Class III static**
Max Capacity	**500 ton**
Resolution	**100,000**
Sampling Rate	**200 times per second**
Display Rate	**12.5 times per second**
Display Unit	**Pound**
Channel Inputs	**1 to 4 channels**
Communication	**RS-232, USB**
Printer	**Built-in thermal**
Power	**Rechargeable battery**
Enclosure	**IP-rated hard case**

TYPICAL APPLICATIONS

- ✓ Aircraft weighing (static)
- ✓ Crane outrigger weighing
- ✓ Haul truck axle weighing
- ✓ Heavy off-road equipment
- ✓ Portable field weighing
- ✓ Compatible load-pad systems

500 TON
MAX CAPACITY

CLASS III
STATIC ACCURACY

RS-232 + USB
OUTPUT PORTS

THERMAL
BUILT-IN PRINTER